Nix Pro 2

Product specifications - v1.3



Form factor

| Weight | 50g (1.8oz) (Accessories not included in weight) |
|------------|--|
| Dimensions | 42mm X 60mm X 60mm (1.65" X 2.36" X 2.36") |
| Materials | Ultrasonically welded PC/ABS blend |
| Haptics | N/A |
| Features | Scratch-resistant glass lens |
| | Dust and water-resistant |
| | Included lanyard for easy carrying |

Performance

| Measurement speed | 1 reported scan/second |
|----------------------------|---|
| Optical resolution | Tristimulus colorimeter (CIE XYZ) |
| Spectral visible range | N/A |
| Repeatability | <0.1 $\Delta E_{_{00}}$ on white (D50, 2°, to mean of 10 measurements every 3 s on white, at a temperature of 23°C) |
| Inter-instrument agreement | Inter-Instrument Agreement: $< 0.4 \Delta E_{00}$ on a selection of wide gamut paint tiles |
| Temperature range | 10°C - 35°C |
| Humidity | 0% – 80% non-condensing |

Optics

| Measurement geometry | 45°:0° optics |
|------------------------|--|
| Measurement port | 14 mm (0.55") diameter |
| Measurement aperture | N/A |
| Illumination spot size | N/A |
| Light source | 4x (2x 5000K and 2x 6500K high-performance, high-CRI, broad-spectrum, white) |
| Adapters | N/A |

Nix Pro 2

Product specifications

Calibration

Each unit individually factory calibrated Integrated/automatic temperature compensation

Reflectance measurement

Measurement Conditions: M2 – UV excluded – ISO 13655:2017

Colorimetry data

CIEXYZ, CIELAB, LCH(ab), RGB, CMYK, and more Reference illuminant and observer: D50/2°, D65/10°

Battery life + charging

USB Micro charging of internal Lithium Polymer Battery

180 day (6 month) standby time per charge (device advertising on BLE)

5,000+ scans per charge

Software development kit

iOS and Android (BLE); Windows (USB) Bluetooth requirements: Bluetooth 4.0

Android: Android SDK level 21 (Android 5.0 Lollipop)

and above. SDK written in Java

iOS: iOS 11.0 and above. SDK written in Objective C SDK contains Bluetooth connectivity routines, commands to request scan in XYZ, or Lab

Packaging + accessories

Micro USB charging cable Nix lanyard Microfiber carrying pouch Quick Start Guide

Connectivity

Bluetooth Low Energy

Warranty + expected product lifespan

12 months from date of sale, warranty for manufacturer's defects (does not cover user damage)

