

Nix Spectro L

Product specifications – v3.1



Form factor

Weight	110 g (3.9 oz) (Accessories not included in weight)
Dimensions	45 mm X 60 mm X 60 mm (1.77" X 2.36" X 2.36")
Materials	Durable, matte grey powder coated aluminum enclosure
Haptics and visuals	Vibration and RGB feedback for charging, connection, and measurement state
Features	Scratch-resistant glass lens Dust and water-resistant Hard point for braided aircraft cable attachment

Performance

Measurement speed	1 reported scan per 2.5 seconds
Optical resolution	9 channel measurement (8 spectral channels plus clear channel)
Spectral visible range	400 – 700 nm, 10 nm resolution reporting (interpolated)
Repeatability	0.1 ΔE_{00} on white (D65, 10°, to mean of 10 measurements every 3 s on white, at a temperature of 23 °C)
Inter-instrument agreement	0.5 ΔE_{00} average, 0.9 ΔE_{00} max. (deviation from Nix Sensor Ltd. standard unit at a temperature of 23 °C on 12 CMYK tint patches (D65, 10°))
Temperature range	10 °C – 35 °C
Humidity	0% – 80% non-condensing

Optics

Measurement geometry	45°:0° ring illumination optics
Measurement port	16 mm (0.63") diameter
Illumination spot size	6 mm (0.24") diameter
Measurement aperture	5 mm (0.20") diameter
Light source	High CRI, broad spectrum LED light source (white, violet and UV)
Adapters	Liquids, powders, gels, and soft surface adapters available

Nix Spectro L

Product specifications

Calibration

Each unit individually factory calibrated
Integrated/automatic temperature compensation
White diagnostics tile included for troubleshooting

Density data

Evaluated according to ISO 5-3:2009
Density status: A, E, I, T
Note: Particular density data availability may differ based on application used.

Battery life + charging

USB-C charging of internal lithium polymer battery
90 day (3 month) standby time per charge (device advertising on BLE)
1,000+ scans per charge

Packaging + accessories

Carrying case
Diagnostics tile
Nix lanyard
USB-C charging cable

Warranty + expected product lifespan

12 months from date of sale, warranty for manufacturer's defects (does not cover user damage).

Reflectance measurement

Measurement conditions:
M0 – UV included – ISO 13655:2017
M1 – D50 – ISO 13655:2017
M2 – UV excluded – ISO 13655:2017

Note: Particular reflectance measurement mode availability may differ based on application used.

Colorimetry data

Evaluated according to ASTM E308-18
CIEXYZ, CIELAB, LCH(ab), RGB, CMYK, and more
Illuminant: A, C, D50, D55, D65, D75, F2, F7, F11
Observer: 2°, 10°

Note: Particular colorimetry data availability may differ based on application used.

Software development kit

Features device connectivity routines, commands to request measurements, and utilities to perform color conversions.

For an up-to-date list of features and supported platforms, visit:
nixsensor.com/nix-software-development-kit/

Connectivity

Bluetooth Low Energy
Legacy USB CDC Serial